O.M.B. No 3067-0077 Expires May 31, 1993

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR).

Instructions for completing this form can be found on the following pages.

•				T
SECTION A PROPERTY INFORMATION				FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME				POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg.		ROUTE AND BOX NUMBER		COMPANY NAIC NUMBER
TOX POLICE 111-02-	0134	Lot 20 X	Lyhwil	d
Prescott			A Z	21P CODE 86304
SECTION B FI	LOOD INSURA	NCE RATE MAP (FIRM)	INFORMATION	
Provide the following from the proper FIRM (See	Instructions):			
1. COMMUNITY NUMBER 2. PANEL NUMBER 040093 1020	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth) 5 4 85 . 7
7. Indicate the elevation datum system used on t 8. For Zones A or V, where no BFE is provided o the community's BFE: feet N	n the FIRM, ar	nd the community has esta	ablished a BFE f	
SECTIO	ON C BUILDI	NG ELEVATION INFORM	IATION	
of 19190. Teet NGVD (or other FIR (b). FIRM Zones V1-V30, VE, and V (with BFE) the selected diagram, is at an elevation of (c). FIRM Zone A (without BFE). The floor used below (check one) the highest grade add (d). FIRM Zone AO. The floor used as the refer one) the highest grade adjacent to the buildidevel) elevated in accordance with the commod. Indicate the elevation datum system used in definition under Comments on Page 2). (NOTE: If the extremely the firm [see Section B, Item 7], then converged to the page 2.)	d as the referer lijacent to the bence level from ing. If no flood nunity's floodpletermining the elevation datumnt the elevation	of the lowest horizontal strain feet NGVD (or other FIR nee level from the selected uilding. In the selected diagram is depth number is available ain management ordinance above reference level elements to the datum system used in the syst	M datum—see Sed diagram is Land diagram is Land diagram is Land diagram is Land diagram is the building vations: May NGV levations is different on the FIRM	ection B, Item 7). feet above or bove or below (check 's lowest floor (reference No Unknown /D '29 Other (describe rent than that used on
4. Elevation reference mark used appears on FIF				
5. The reference level elevation is based on: Kanada (NOTE: Use of construction drawings is only valid for the build be required once construction is complete.)	ralid if the build Iding during the	ling does not yet have the e course of construction.	reference level A post-construct	ion Elevation Certificate
5. The elevation of the lowest grade immediately Section B, Item 7).	adjacent to the	building is: 5141881	feet NGVD	or other FIRM datum-see
SE	CTION D CO	MMUNITY INFORMATIO	N	
1. If the community official responsible for verifyin is not the "lowest floor" as defined in the comm floor" as defined by the ordinance is:	unity's floodpla	ain management ordinand GVD (or other FIRM datu	e, the elevation	of the building's "lowest

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME KENNETH E. SPEDDING

TITLE

DISTRICT DIRECTOR

COMPANY NAME YAVAPAI COUNTY FLOOD CONTROL DISTRICT

ADDRESS

255 E. GURLEY ST.,

PRESCOTT

SIGNATURE

COMPANY NAME YAVAPAI COUNTY FLOOD CONTROL DISTRICT

AZ

AZ

B6301

ZIP

SIGNATURE

SIGNATURE

COMPANY NAME YAVAPAI COUNTY FLOOD CONTROL DISTRICT

AZ

B6301

ZIP

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

COMMENTS: Diagram #3 was used, however, there is no intermediate level. There is a lower and upper level.

The lower level is considered a walkout basement, which is unfinished, and contains no equipment servicing the structure. The area is used for storage only and there are openings to allow for the conveyance of flood waters. The structure is only below grade on three sides, thus, technically, per FEMA it is not a basement. Also, the reference level used is the finished floor of the upper level. This area was an approximate Zone A. Currently, the District has and is using the approved preliminary FIS study for this area. The date of the FIRM indicated

on Page 1 of this Certificate is the Preliminary Panel date ON PILES, WITH ON PIERS, OR COLUMNS BASEMENT SLAB ZONES ZONES ZONES ZONES REFERENCE REFERENCE LEVEL REFERENCE BASE LEVEL FLCCO BASE REFERENCE FLCCO ADJACENT ELEVATION LEVEL LEVEL ADJACENT:

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.